WELFARE ELECTRONIC COMPONENT LTD.



UNIT C, G/F., MING CHU BLDG., 195-201 APLIU STREET, SHAMSHUIPO, KOWLOON, HONG KONG. TEL:(852) 2786 0763 (HOT LINE), 2371 0368(6 LINES) FAX:(852)-2786 0872

CA-130 60W Mobile Amplifier



- CA-130 60W Mobile Amplifier
- Easy installation in practically any 12V battery equipped car.
- Compact, rugged construction and front panel controls.
- Two phone jack mic. inputs and handy phone jack
 AUX input for external equipment connection.
- Unidirectional dynamic microphone with talk switch.

Specification	
Power Source	Standard voltage: 14VDC
	Usable Voltage; 10 ~ 16V DC (12V Battery Used)
Power Consumption	4.4A or less at rated power output.
Output Power	Rated 30W, max. 60W
Output Impedance	40 (BRN), 80 (ORG), COmmon (WHT)
	Changeable by changing lead wire connections.
Distortion	Less than 5% (at 1kHz rated output)
Frequency Response	100 ~ 10,000Hz
Input	Mic 1, 2 : 6000, 4 mV, Phone Jack
	Aux: 10 kO, 500 mV, Phone Jack
Dimensions	(W x H x D): 178 x 50 x 144mm (mounting device
	excluded)
Weight	1.1 kg
Finish	Front panel; ABS resin, Black
	Case; Zinc plated steel sheet
Accessory	Microphone holder 1
	Mounting Bracket 1
	Mounting Screw 1
	Fuse (8A) 1
	Connection cord 1 set
Accessory Microphone	Unidirectional dynamic type with Talk switch
	Impedance : 6000
	Sensitivity: -53dB (IkHz, 0 dB = 1 V / Pa)