

PXR-52 Series

Weatherproof Proximity Reader



FEATURES

- Compact and advanced design.
- Quick response, low interference, low power consumption and highly stable.
- Reading range up to 15 cm without interference.
- Interface: ABA T2, Wiegand 26 bit, RS-485.
- Weather proof, Suitable to use in all places.
- Provide LED & Buzzer control input and can fit all controllers.
- The Case sensor provide the controller to guard against remove, when destroy by violence, the warning message will be show.

SPECIFICATIONS

HARDWARE	52ET	52ETK	52EW	52EWK	52ES	52ESK
Communication interface	T2	T2	W	W	485	485
	T2=ABA Track 2 / W=Wiegand / 485=RS-485					
485 Baud rate	19200bps-N-8-1					
Keypad	----	V	----	V	----	V
Input device	1 (Case sensor)					
Frequency	125KHz					
Indicators	1 dual color LED (Power / Status)					
Beep tone	Buzzer					
Reading range	15cm (max)					
ELECTRICAL						
Operating voltage	DC 12V @ 200mA					
Power consumption	1.5W (max)					
ENVIRONMENTAL						
Operating temperature	0°C~55°C / 32°F~131°F					
Relative humidity	20%~95%(Non condensing)					
PHYSICAL						
Dimensions	76mm(W) x 120mm(L) x 23mm(H)					
Weight	130g					

HUNDURE

www.hundure.com

The manufacture reserves the right to revise this publication without obligation to notify any person or organization of such revisions.

PXR-52 Series-CE-20030925