




PROLOCK SYSTEM OF CANADA



NCR Industrial Centre, 250 Baseline Road E. Bowmanville, ON L1C 1A4 CANADA

4303 鐵門、木門專用電鎖口(NO功能)




4304 鐵門、木門專用電鎖口(NC功能)

Key Specifications/Special Features:


- Door lock
- Fail secure electric strike with auto relock & monitoring (4303)
- Fail safe electric strike with auto relock & monitoring (4304)
- (4303) 12VDC, work current 250mA, stand by current 0mA
- (4304) 12VDC, work current 200mA, stand-by current 200mA
- Weight 0.4kg
- L: 150mm, W: 25mm, H: 33mm

4303: 通電開門, 斷電閉門
具有監測信號, 回鎖功能
鎖口為不銹鋼摺片
輸入電壓: 12VDC
工作電流: 250mA, 靜態電流: 0mA
重量: 0.4kg
呎吋(長闊高): 150 x 25 x 33mm

4304: 通電閉合, 斷電開啟
具有監測信號, 回鎖功能
鎖口為不銹鋼摺片
輸入電壓: 12VDC
工作電流: 200mA, 靜態電流: 200mA
重量: 0.4kg
呎吋(長闊高): 150 x 25 x 33mm



934GL



無框玻璃門電鎖夾(NC功能)

Key Specifications/Special Features:

- Door lock
- Fail safe electric strike for fully glazed door(12mm-15mm by option)
- 12VDC, work current 250mA, Stand-by current 200mA
- Weight 0.4kg
- L: 160mm, W: 25mm, H: 31mm

無框玻璃門夾鎖
通電閉合, 斷電開啟
輸入電壓: 12VDC
工作電流: 250mA
靜態電流: 200mA
重量: 0.4kg
呎吋(長闊高): 160 x 25 x 31mm



9030




專業電鎖變壓器附延時功能

Key Specifications/Special Features:

- Electric Lock Power Supply
- Input: 220v 60Hz
- Output: DC 12VDC with Timer
- With NO & NC Feature
- With 3Amp power supply
- Weight: 1.60kg
- L: 200mm, W: 90mm, H: 70mm

外接式連線, 安裝方便
保險絲保護, 防止短路造成電源燒毀,
可接二把電鎖, 開鎖時間可調0-60秒
輸入電壓: 220V
輸出電壓: 12VDC
重量: 1.60kg
呎吋(長闊高): 200 x 90 x 70mm



1092U




無框玻璃門低溫電插鎖(NC功能)


Key Specifications/Special Features:

- Door lock
- Fail safe electric bolt for fully glazed door
- With monitoring feature
- 12VDC, work current, 1000mA
- Stand-by current 300mA
- Weight 1.4kg
- L: 180mm, W: 50mm, H: 52mm

U型上下無框玻璃門專用雙向
電插鎖(低溫式)
輸入電壓: 12VDC
工作電流: 1,000mA
靜態電流: 300mA
重量: 1.4kg
呎吋(長闊高): 180 x 50 x 52mm



EM5207




明裝磁力鎖


Key Specifications/Special Features:

- Door lock
- Single door EM lock (surface mount)
- Holding force 300kg
- 12VDC, work current 450mA,
- Stand-by current 350mA
- Weight 1.9kg
- L: 250mm, W: 48mm, H: 25mm

明裝磁力鎖
磁拉力達300kg
輸入電壓: 12VDC
工作電流: 450mA
靜態電流: 350mA
重量: 1.9kg
呎吋(長闊高): 250 x 48 x 25mm
(可選購附LED功能)



5208M



暗裝磁力鎖

Key Specifications/Special Features:

- Door lock
- Single door EM lock (mortise mount)
- Holding force 300kg
- 12VDC, work current 450mA, Stand by current 350mA
- Weight 1.9kg
- L: 236mm, W: 38mm, H: 26mm

暗裝磁力鎖
磁拉力達300kg
輸入電壓: 12VDC
工作電流: 450mA
靜態電流: 350mA
重量: 1.9kg
呎吋(長闊高): 236 x 38 x 26mm



H4000




感應式密碼雙功能鍵盤


Key Specifications/Special Features:

- Programming reader digital keypad
- Standalone or online system
- Tamper contact
- Maximum to linkup with 256 door to use
- Disable code for programming time periods
- Code reprogramming disable option
- Weight 0.2kg
- L: 118mm, W: 106mm, H: 30mm

感應式密碼雙功能鍵盤
單獨使用或聯網上電腦控制兩款選擇
連接H4002可接32個門
系統最多可接256個門
可選中文軟件(H4001型)
可選考勤功能
可與停車場系統連接
及其它連成一卡通使用
重量: 0.2kg
呎吋(長闊高): 118 x 106 x 30mm



2160T



T型電插鎖(NC功能)

Key Specifications/Special Features:

- Door lock
- Fail safe electric bolt
- Adjustable ball type with CE approval
- 12VDC, work current 800mA
- Stand-by current 650mA
- Weight 0.6kg
- L:125mm, W:32mm, H:118mm

工作方式: 磁珠式
通電閉合, 斷電開啓
輸入電壓: 12VDC
工作電流: 800MA
靜態電流: 650MA
呎吋(長闊高): 125 x 32 x 118mm

