

## HS 5140



**STEINEL sensor-switched halogen floodlights are the ideal solution when it comes to illuminating the front of buildings, driveways and vulnerable spots with particularly bright light.**

The vigilant floodlights are factory-fitted with bulbs of different ratings ranging from 150 to 500 watts. This automatically picks out special features, welcomes guests and frightens off unwanted visitors. Ranging from the low-price Fresnel lens light HS 5140 to the microprocessor controlled hi-tech floodlight HS 500, the STEINEL line-up offers just the right model for any application. Models HS 150 and HS 300 are equipped with a ceramic reflector.

### Settings

- The detection zone can be adjusted exactly to requirements at the site of installation by means of the tilting, swivelling multi-lens (HS 150 DUO, HS 300 DUO, HS 500 DUO) or Fresnel lens (HS 5140) and can be limited using the shrouds provided.
- Control dial for easy adjustment of light "ON" duration and twilight threshold.

### HS 5140



Detection zone



Function settings

### HS 5140

Prod. No. <b>black</b>	<b>575212</b>
Prod. No. <b>white</b>	<b>577919</b>
Dimensions (h x w x d)	185 x 170 x 160 mm
Output	500 W max.
Voltage	230 – 240 V / 50 Hz
Angle of coverage	140° with sneak-by guard
Adjustment range	180° vertically to front and rear
Reach	12 m max. (temperature-stabilised)
Twilight setting	2 – 2000 lux
Time setting	10 sec. – 15 min.
Enclosure	IP 54
Bulb	Including 500 W bulb (R7S halogen bulb)
Optional accessories	–

