

UT58E

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(0.05\%+3)$
AC Voltage	2V/20V/200V/1000V	$\pm(0.5\%+10)$
DC Current	2mA/200mA/20A	$\pm(0.5\%+5)$
AC Current	20mA/200mA/20A	$\pm(0.8\%+10)$
Resistance	200 Ω /2k Ω /20k Ω /2M Ω /200M Ω	$\pm(0.5\%+10)$
Capacitance	2nF/20nF/2 μ F/20 μ F	$\pm(3\%+40)$
Temperature (°C)	-40°C~1000°C	$\pm(1\%+30)$
Frequency	20kHz	$\pm(1.5\%+5)$

Special Functions

Diode	✓
Continuity Buzzer	✓
Transistor	✓
Data Hold	✓
Full Icon Display	✓
Sleep Mode	✓
Low Battery Display	✓
Input Impedance for DC Voltage Measurement	Around 10M Ω
Max. Display	19999



UT58E

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54 mm
Product Colour	UT58E - Grey Hoister - Red
Product Net Weight	350g (including hoister)
Product Size	: 79 x 88 x 39 mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip, Multi-Purpose Socket, Hoister
Standard individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	490 x 425 x 300 mm (0.062 CBM Per Standard Carton)
Standard Carton Gross Weight	: 9kg