

PRODUCTS

- Multimeters
- Voltage Testers
- Clamp Meters
- Clamp Adaptors
- Multi-Trans, Energizer
- Loggers
- Insulation Testers
- Earth Testers
- LOOP/PSC Testers
- RCD Testers
- Multi Function Testers
- Combi Tester
- Portable Appliance Testers
- Power Meters
- Clamp Sensors
- Others
- Test Leads
- Discontinued Products


Digital Insulation / Continuity Tester
MODEL 3007A

- Bargraph to display insulation resistance.
- Displays the value of external AC voltage along with flashing symbol.
- Auto null function to automatically subtract the test lead resistance before displaying the real continuity resistance value.
- Trac-Lok mode to conserve battery life on insulation and continuity tests.
- Live circuit warning beeper.
- Releasing the test button automatically discharges the charges stored in the circuit under test.
- Backlight function to view the test results in dimly lit areas.
- 200mA continuity measuring current to IEC 61557.
- Minimum 1mA current on insulation tests to IEC 61557.



Insulation Resistance	
Test Voltage	250V/500V/1000V
Measuring Ranges (Mid-scale Value)	20MO/200MO/2000MO
Output Voltage on open circuit	Rated test voltage+20%, -0%
Nominal Current	1mA DC min.
Output Short Circuit Current	1.5 mA DC approx.
Accuracy	± 1.5%rdg± 5dgt (20MO/200MO) ± 10%rdg± 3dgt (2000MO)
Continuity Test	
Measuring Ranges (Mid-scale Value)	20O/200O/2000O
Output Voltage on open circuit	7~12V DC
Measuring Current	200mA DC min.
Accuracy	± 1.5%rdg± 5dgt (20O) ± 1.5%rdg± 3dgt (200O/2000O)
AC Voltage	
AC Voltage range	0-600V AC
Accuracy	± 5%rdg± 3dgt
General	
Safety Standard	IEC61010-1 CAT.III 300V Pollution Degree 2 IEC61010-2-031 IEC61557-1/2/4
IP Rating	IEC60529-IP54
EMC Standard	IEC61326-1
Withstand Voltage	3700V AC for 1 minute
Power Source	R6P(AA)(1.5V) × 8
Dimensions	185(L) × 167(W) × 89(D)mm
Weight	990g approx
Accessories	7122 (Test leads) Pouch for test leads 8923 (F500mA/600V fuse) × 2 R6P(AA) × 8 Shoulder Strap

