

PRODUCTS



- [Multimeters](#)
- [Voltage Testers](#)
- [Clamp Meters](#)
- [Clamp Adaptors](#)
- [Multi-Trans, Energizer](#)
- [Loggers](#)
- [Insulation Testers](#)
- [Earth Testers](#)
- [LOOP/PSC Testers](#)
- [RCD Testers](#)
- [Multi Function Testers](#)
- [Combi Tester](#)
- [Portable Appliance Testers](#)
- [Power Meters](#)
- [Clamp Sensors](#)
- [Others](#)
- [Test Leads](#)
- [Discontinued Products](#)

MODEL **5406A**

- Custom microprocessor controlled for highest accuracy and reliability.
- 3 LEDs for checking correct wiring status.
- 0 and 180 degree phase angle switch permits quick tests and consistent readings.
- Digital read-out of tripping time.
- Test DC sensitive breakers.
- Constant current source circuitry ensures that a fluctuating mains voltage does not affect the accuracy of readings.
- Large custom digital display readout.
- Visual indication of reversed phase and neutral wiring at socket.
- Designed to IP54 Rating.
- Complies with IEC61557



Rated Tripping Current	10/20/30/200/300/500mA
Fault Condition Settings	× 1/2, × 1, × 5, × DC, AUTO RAMP
Trip Current Duration	1000ms, 200ms(×5)
Lowest Resolution	1ms
Trip Time Accuracy	± 0.6%rdg ± 4dgt
Operating Voltage	230V+10%-15% (195V~253V) 50Hz
Safety Standard	IEC61557-1,-6 IEC61010-1 CAT.III 300V IEC61010-2-031 Pollution Degree 2
Withstand Voltage	3700V AC for 1 minute
IP Rating	IEC60529-IP54
Dimensions	186(L) × 167(W) × 89(D)mm
Weight	800g approx.
Accessories	Molded plug test leads Pouch for test leads Shoulder Strap Instruction Manual
Optional	7121 (Distribution board test leads)