

Technical Data

DE-FLUX 160 FLUX REMOVER/PCB CLEANER

DE-FLUX 160 is a unique blend of solvents, formulated specifically for removal of fluxes and residues.

APPLICATIONS

Removes all organic and inorganic fluxes and residues from PCBs and electronic components. Penetrates thoroughly into contamination and evaporates completely after use, leaving parts clean and dry.

N.B. Not for use on live electrical equipment. Allow solvent to evaporate completely before operating the equipment.

May affect certain plastics. Always test a small, inconspicuous area before general use.

TECHNICAL DATA

Appearance	:	Clear, colourless liquid
Odour	:	Sweet, characteristic
SG @ 25°C	:	0.66
Pressure @ 25°C	:	3.5 Bar
Discharge rate	:	1.1 g/sec
Initial boiling point	:	55°C
Flammability	:	Classified as extremely flammable under CHIP Regulations
Flashpoint	:	Not applicable in sealed aerosol
Packaging	:	200ml aerosol

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 12 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

MISREPRESENTATION ACT 1967**TRADE DESCRIPTIONS ACT 1968**

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.